
# GOT3187W-881-PCT

18.5" WXGA TFT Fanless Multi-Touch Panel Computer with LGA1150 Socket 4th Gen Intel® Core™ i7/i5/i3. Celeron® & Pentium® Processor (0°C to +40°C)

# **Features**

- 18.5" WXGA projected capacitive multi-touch screen
- Fanless design with LGA1150 socket 4th gen Intel® Core™ i7/i5/i3 & Celeron® processor (Haswell)
- 2.5" 7/9.5 mm SATA HDD, CFast™ and mSATA
- WLAN module & antenna (optional)
- 2 Gigabit LAN, 2 USB 3.0, 2 USB 2.0 & 2 COM ports
- IP65 front bezel and rugged design
- Supports panel mount and optional VESA arm/desktop stand/ wall mount
- 2 PCI Express Mini card slots























#### Introduction

The GOT3187W-881-PCT adopts an 18.5-inch WXGA LCD and supports LGA1150 socket 4th generation Intel® Core™, Pentium® and Celeron® processors. It can run Windows® 7, Windows® 7 Embedded, Windows® 8, Windows® 8 Embedded for a variety of applications. This industrial touch panel PC has abilities below to make it surely a robust and reliable solution.

#### **High Performance Haswell Processor**

The GOT3187W-881-PCT supports LGA1150 socket 4th generation Intel® Core™ and Celeron® Haswell processors. Users can choose different processor upon request. It also supports up to 8 GB DDR3-1333/1600 MHz memory modules. Rich I/O includes dual PCI Express Mini card slots, 2.5" HDD drive bay, USB 3.0 port, RS-232/422/485 and HDMI interface


#### Reliable and Stable Design

The GOT3187W-881-PCT is a fanless cooling panel system designed for industrial machinery market. The Intel® Haswell panel PC can work under 1.0G (10 to 500Hz, random for CFast™ card) in operation mode with a patent of anti-vibration design. The patent improves the system reliability and sustainability.

#### 18.5-inch WXGA LCD with Projected Capacitive Multi-touch

The 18.5" WXGA IP65-rated touch panel PC supports 300 nits brightness and can display contents in HD resolution. With projected capacitive multi-touch screen, users can operate more directly and friendly. The hardness of touch glass surface is up to 7h and is better for anti-scratch purpose





- 1. Power switch (ATX)
- 2. Power input connector
- 3. Audio (Line-out)
- 4. Audio (Mic-in)
- 5. COM1/2 (RS-232/422/485)
- 6. HDMI output
- 7. Gigabit LAN x 2
- 8. USB 2.0 x 2
- 9. USB 3.0 x 2 10. CFast™ card slot
- 11. Antenna x 3
- 12. LED backlight power on/off
- 13. Brightness +
- 14. Brightness -

## **Specifications**

Front Bezel	IP65 front bezel	
LCD Panel	Display Type	18.5" WXGA TFT LCD
	Brightness (cd/m²)	350 nits
	Resolution	1366 x 768
Main System	CPU	LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor (Haswell), up to 45 W TDP
	Chipset	Intel® H81
	System Memory	1 x 204-pin DDR3 1333/1600 SO-DIMM, up to 8GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 2.5" 7/9.5 mm SATA HDD 1 x CFast™ card 1 x mSATA
	Watchdog Timer	255 levels, 0 to 255 sec.
	Onboard Graphics	Integrated Intel® HD Graphics

## **Specifications**

оросинации	
I/O Connector	2 x RS-232/422/485 (COM 1/2) 1 x Switch for power on/off (ATX)
	2 x Audio (Line-out & Mic-in)
	2 x USB 3.0
	2 x USB 2.0
	1 x HDMI
	2 x 10/100/1000 Mbps Ethernet (Intel® i210-AT & i217-V)
TPM	N/A
Expansion Interface	2 x PCI Express Mini Card slot
Touchscreen	Projected capacitive multi-touch
Power Supply	19 VDC with adapter
Power Consumption	109 W
Dimensions	460 mm (18.1") (W) x 89.5 mm (3.5") (D) x 285 mm (11.2") (H)
Packing Dimensions	600 mm (23.58") (W) x 195 mm (7.67") (D) x 500 mm (19.68") (H)
Weight (net/gross)	6.3 kg (13.9 lb) /8.3 kg (18.29 lb)
Environment	Operating temperature: 0°C to +40°C (+32°F to +104°F)
	Relative humidity: 20% to 90% @ 40°C; non-condensing
	Operation vibration:
	1.0G, 10 to 500 Hz, random for CFast™ card
Certificate	CE

# **Packing List**

- 1 x GOT3187W-881-PCT 1 x Driver CD
- 1 x Adapter
- 1 x Panel mount kit

# **Ordering Information**

18.5" WXGA TFT fanless touch panel computer with LGA1150 socket Intel® 4th generation Core™ 17/15/13, Pentium® & Celeron® processor, projected capacitive multi-touch screen and AC-DC 19 VDC power adapter (power
DIN 4P connector)

# **Optional Accessories**

Wi-Fi	
4G	
82231770050E	GOT3177T-834 wall mount kit

# **Optional EOS Installation**

WE8S	
WES 7	
Windows® 10 IoT Enterprise	

## **Optional OS Installation**

Vindows® 8.1
Vindows® 7
Vindows® 10



▲ Ideal for factory automation & self-service kiosk in retail

#### **Dimensions**

