# P1157S-881


15" XGA TFT Slim Industrial Touch Panel Computer with 4th Gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® Processor

# **Features**

- 15" XGA TFT LCD display
- LGA1150 socket 4th gen Intel® Core™ i7/i5/i3 Celeron® & Pentium® processor (Broadwell/Haswell)
- Intel® H81 chipset
- Less screw design for easy installation
- 2 USB 3.0, 4 USB 2.0 and 4 COM ports
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust aluminum with IP65 compliant front bezel design
- The best C/P ratio for HMI solution







- 1. COM 1 with 5V & 12V (RS-232/422/485)
- 2. COM 3 with 5V & 12V (RS-232/422/485)
- 3. LAN 1 (RJ-45 for Gigabit Ethernet)
- 4. LAN 2 (RJ-45 for Gigabit Ethernet) 5. COM 4 with 5V & 12V (RS-232)
- 6. HDMI x 1
- 7. COM 2 with 5V & 12V (RS-232/422/485)
- 8. VGA x 1 9. USB 3.0 x 2
- 10. USB 2.0 x 2
- 11. Mic-in x 1, Line-out x 1
- 12. USB 2.0 x 2
- 13. AC Plug x 1
- 14. Switch for power on/off x 1







# Introduction

The P1157S-881 is a multimedia 15" touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the P1157S-881 is powered by a high performance LGA1150 socket 4th generation Intel® Core™ i7/i5/i3 Celeron® & Pentium® processor with the Intel® H81 Express chipset (Broadwell/Haswell). It features four COM ports, two Gigabit Ethernet and up to 16 GB memory of dual-channel DDR3 that delivers high computing capability for high performance-demanding applications. The industrial panel PC is most suitable for kiosk, factory and automation.

#### **Dual Monitor Display**

If larger viewing area is desired, an additional display can be connected via the system's VGA or HDMI port to help enhance worker's productivity level.

#### Speaker and WLAN Antenna Supported

The P1157S-881 features built-in speakers for kiosk application to display multimedia content program. It also supports WLAN module antenna (optional) for wireless network connectivity.

#### Friendly Less Screw Design

The P1157S-881 is designed with ease of maintenance in mind. There are only three screws on the back chassis, so that technicians can quickly remove the system's back cover with minimum effort.

#### **Specifications**

Front Bezel	Aluminum with IP65	Aluminum with IP65/NEMA 4 rugged protection	
LCD Panel	Display Type	15" XGA TFT LCD	
	Brightness	250 nits	
	Resolution	1024 x 768 pixels	
	Viewing Angle	160°/140°	
Main System	CPU	LGA1150 socket 4th generation Intel® Core™ i7/i5/i3 Celeron® & Pentium® processor (Broadwell/ Haswell)	
	Chipset	Intel® H81	
	System Memory	2 x 204-pin DDR3-1333/1600 SO-DIMM, up to 16GB	
	BIOS	AMI UEFI BIOS with OA 3.0 built	
	Storage	1 x 3.5" or 2 x 2.5" 7/9.5 mm SATA HDD	
	Watchdog Timer	255 levels, 1 to 255 sec.	

### **Specifications**

opouniourioni		
IO Connector	3 x RS-232/422/485 with 5V & 12V 1 x RS-232 with 5V & 12V 1 x VGA 1 x HDMI 2 x USB 3.0 4 x USB 2.0 2 x 10/100/1000 Mbps Ethernet (Intel® i217-V & i210-AT) 1 x Audio (Mic-in/Line-out)	
TPM	N/A	
Expansion Interface	N/A	
Touchscreen	5-wire resistive type Light transmission 79% 1 million activations (typical) at a single point	
Power Supply	100 to 240 VAC, 200W	
Power Consumption	142W	
Dimensions	378 mm (14.88") (W) x 72.2 mm (2.84") (D) x 309 mm (12.17") (H)	
Packing Dimension	610 mm (24.02") (W) x 260 mm (10.24") (D) x 590 mm (23.23") (H)	
Weight(net/gross)	5.4 kg (11.88 lb)/ 7.8 kg (17.16 lb)	
Environment	Operating temperature: 0°C to +45°C (+32°F to +113°F) Relative humidity: 10% - 90% @ 40°C, non-considering Operating vibration: 1.0G, 5-500Hz, random	
Certificate	CE	

# **Packing List**

- 1 x P1157S-881
- 1 x Driver CD
- 6 x Panel mount kit

# **Ordering Information**

P1157S-881	15" XGA slim industrial touch panel computer with LGA1150 socket 4th generation Intel® Core™ i7/i5/i3, Pentium® &
	Celeron® processor, resistive touch screen and 100 to 240 VAC

<sup>\*</sup> Specification and certifications are based on options and may vary.

# **Optional Accessories**

WiFi kit		
82211570050E	VESA & wall mount kit	
82211570060E	Rack mount kit	
72211571000E	2 x 2.5" HDD bracket	
E981604011	ATC10 (VESA arm clamp type)	
E981604012	ATW10 (VESA arm wall mount)	
E226171119	PPC S1702B black stand (S)	
	Power cord (EU/US/UK/JP)	

# **Optional OS Installation**

Windows® 7/8.1 Windows® Embedded 7/8



▲ Less screw design

#### **Dimensions**

